

Food Safety Thermometers



Bimetal Type - 1" Dial – 5" Stem

Miljoco Pocket Test Thermometers are ideal for use as test instruments in the HVAC, plumbing, refrigeration, and appliance repair industries. These thermometers are furnished with a durable plastic carrying case and pocket clip. They are also available with either a domed or magnifying lens and can be recalibrated easily in the field. Various ranges are NSF® listed for use in the food service industry.

General Specifications

CASE: Hermetically sealed 300 series stainless steel

LENS: Acrylic

DIAL: Aluminum, white finish and black markings

POINTER: Red

RECALIBRATOR: External adjusting hex nut or recalibrator lug on rear of case

STEM: 300 series stainless steel, Ø 0.250".

ACCURACY: ±1% full range

AMBIENT TEMPERATURE: -40 to 140°F (-40 to 60°C).



B1098M82C-5.0

Models & Dimensions (in.)

Model	Range	Dial Size	Stem Length	Lens Type	Adjustment Type
B1098M90C-5.0	-40 to 160°F	1"	5"	Magnifying	Recalibrator Lug
B1098M82C-5.0	0 to 220°F*	1"	5"	Magnifying	Recalibrator Lug
B1098M43C-5.0	25 to 125°F*	1"	5"	Magnifying	Recalibrator Lug
B1098M95C-5.0	50 to 500°F	1"	5"	Magnifying	Recalibrator Lug
B1098M28C-5.0	0 to 100°C	1"	5"	Magnifying	Recalibrator Lug
B1098M42C-5.0	-40 to 70°C	1"	5"	Magnifying	Recalibrator Lug
B1098D90A-5.0	-40 to 160°F	1"	5"	Domed	Hex Nut
B1098D82A-5.0	0 to 220°F*	1"	5"	Domed	Hex Nut
B1098D43A-5.0	25 to 125°F*	1"	5"	Domed	Hex Nut
B1098D95A-5.0	50 to 500°F	1"	5"	Domed	Hex Nut
B1098D28A-5.0	0 to 100°C	1"	5"	Domed	Hex Nut
B1098D42A-5.0	-40 to 70°C	1"	5"	Domed	Hex Nut

* - NSF® listed range

Food Safety Thermometers

Pocket Test Type



Pocket Thermometer with Magnifying Lens

- ☐ Stainless Steel Case
- ☐ 1" White Dial with Black Markings
- ☐ 5" long stem, Ø 0.150"
- ☐ Red Pointer
- ☐ Recalibration Lug
- ☐ White Plastic Sheath
- ☐ NSF® Listed



Models

Model	Range
B1098M90C-5.0	-40 to 160°F
B1098M82C-5.0	0 to 220°F*
B1098M43C-5.0	25 to 125°F*
B1098M95C-5.0	50 to 500°F
B1098M28C-5.0	0 to 100°C
B1098M42C-5.0	-40 to 70°C

*NSF® listed range

Pocket Thermometer with Domed Lens

- ☐ Stainless Steel Case
- ☐ 1" White Dial with Black Markings
- ☐ 5" long stem, Ø 0.150"
- ☐ Red Pointer
- ☐ Recalibration Hex Nut
- ☐ White Plastic Sheath
- ☐ NSF® Listed



Models

Model	Range
B1098D90A-5.0	-40 to 160°F
B1098D82A-5.0	0 to 220°F*
B1098D43A-5.0	25 to 125°F*
B1098D95A-5.0	50 to 500°F
B1098D28A-5.0	0 to 100°C
B1098D42A-5.0	-40 to 70°C

*NSF® listed range



Refrigerator Case Thermometer

- ☐ Stainless Steel Case
- ☐ 1" White Dial with Black Markings
- ☐ Ø 0.150" Stem W/ 1/4-28 Connection
- ☐ Installation Nut
- ☐ Red Pointer
- ☐ Recalibration Hex Nut
- ☐ NSF® Listed



Models

Model	Stem Length
B1098D18D-2.5	2½"
B1098D18D-3.5	3½"
B1098D18D-5.0	5"

Accessories

- ☐ Part # 65-11 – 2-Hole Mounting Flange

CD109885 Digital Pocket Test Thermometer

- ☐ 1¼" Brown Plastic Case
- ☐ 5" long stem, Ø 0.150"
- ☐ Adjustable between F/C
- ☐ On/Off Switch
- ☐ -58 to 302°F & -50 to 150°C



Pocket Thermometers DS-B1098D EN v1 Dataheet 0826