SERIES CDTR | CARBON DIOXIDE/TEMPERATURE TRANSMITTERS



North American style wall mount



DSA compliant option -S



Duct mount

FEATURES/BENEFITS

- **Minimize inventory and save time by combining CO_2, temperature and humidity measurements into one transmitter**
- **Requires minimal maintenance with Automatic Baseline Correction (ABC) to account for sensor drift**
- **Reduce operation costs using a low energy, reliable, and repeatable CO_2 sensor**
- **Simplify installation with backplate electrical connection**

APPLICATIONS

- Demand control ventilation in schools, office buildings, hospitals, and other indoor environments
- LEED® certification

DESCRIPTION

The **Series CDTR Carbon Dioxide and Temperature Transmitters** accurately monitor the CO_2 concentration and temperature in indoor environments to help achieve energy savings. In order to achieve a higher level of accuracy, the Series CDTR includes barometric pressure adjustment. The CO_2 universal output allows users to select the transmitter output to be 4-20 mA, 0-5 VDC, or 0-10 VDC to work with virtually any building management controller.


For applications that require visual indication, the wall mount configurations of the Series CDTR can be ordered with an integral LCD display. To prevent tampering, the action of the buttons can be locked out using an internal dip switch selection.

The Series CDTR CO_2 transmitters are available with a -S option that provides the necessary attributes and parameters to be compliant with DSA requirements for monitoring CO_2 levels in schools. There is a front facing LED that illuminates when the CO_2 level exceeds 1100 PPM.


SPECIFICATIONS

Sensor	NDIR, 15 year life expectancy.
Range	CO_2: 0 to 2000 or 0 to 5000 PPM (depending on model); Temperature: 32 to 122°F (0 to 50°C).
Accuracy*	CO_2: ±40 PPM + 3% of reading (2000 PPM CO_2); ± 50 PPM + 5% of reading (5000 PPM CO_2); Temperature: ±1°C @ 25°C.
Response Time	2 min for 90% step change.
Temperature Limits	32 to 122°F (0 to 50°C).
Humidity Limits	0 to 85% (non-condensing).
Power Requirements	16-35 VDC or 19-28 VAC.
Power Consumption	Average: 2 w; Peak: 3.75 w.
Output	Current: 4-20 mA (max. 500 Ω); Voltage: 0-5 VDC or 0-10 VDC (min. 500 Ω); Relay: SPST NO rated 2A @ 30 VDC; RTD or thermistor per r-t curves on page 4 (depending on model).
Compliance	CE.
*The specified CO_2 accuracy is only guaranteed after three weeks of continuous operation in environments which are intermittently occupied.	

DIMENSIONS



North American style wall mount



Duct mount

HOW TO ORDER

Use the **bold** characters from the chart below to construct a product code.

CDTR **-2** **N** **4** **4** **-LCD**

SERIES
CDTR: Carbon dioxide/temperature transmitter

RANGE
-2: 0 to 2000 PPM CO_2 range
-5: 0 to 5000 PPM CO_2 range

CONFIGURATION
N: North American style wall mount
D: Duct mount

CO_2
4: 4-20 mA / 0 to (5 or 10) VDC

OPTIONS
-FC: Factory calibration certificate
-LCD: LCD display (wall only)
-RLY: Relay
-S: School

TEMPERATURE OUTPUT
0: None
4: 4-20 mA / 0 to (5 or 10) VDC
A: 10 KΩ NTC thermistor type III
B: 10 KΩ NTC thermistor type II
D: Pt100 Ω RTD
E: Pt1000 Ω RTD
F: 20 KΩ NTC thermistor

ACCESSORIES

Model	Description
A-449	Remote LCD display allows remote indication of select Dwyer® wall mount transmitters for validation or certification purposes
A-449A	Remote LCD display with buttons allows remote indication and calibration of select Dwyer® wall mount and duct mount transmitters for validation and certification purposes

LEED® is a registered trademark of the U.S. Green Building Council.

ORDER ONLINE TODAY!
dwyer-inst.com

DWYER INSTRUMENTS, LLC

©Copyright 2022 Dwyer Instruments, LLC
Printed in U.S.A. 12/22

DS-CDTR Rev. 1

Important Notice: Dwyer Instruments, LLC reserves the right to make changes to or discontinue any product or service identified in this publication without notice. Dwyer advises its customers to obtain the latest version of the relevant information to verify, before placing any orders, that the information being relied upon is current.